

Annex 3 - Products technical specifications

Item #1: Bin liners, black

Screwfix BIN LINERS

Color: black

Capacity: 50ltr

Pack size: 50

Item #2: Brush, hand, with dustpan

LARGE DUSTPAN AND BRUSH BLACK / YELLOW

Heavy duty dustpan and brush with both stiff and soft PVC flagged bristles. Integrated rubber lip must mould to the floor surface to aid in the collection of finer particles. Serrated edges clean dust and dirt from the hand brush.

Item #3: Brush, stiff

STIFF WOODEN BROOM 18" (450MM)

Outdoor, polypropylene sweeping broom with bracket and wooden handle. Ideal for removal of light and heavy debris in wet or dry conditions.

- Polypropylene
- 450mm PVC Broom Head

Item #4: Bucket for mopping

MOBILE MOP BUCKET YELLOW 20LT

Lightweight, durable mop bucket with 4 corner castors for excellent maneuverability. Features detachable press and separate clean and dirty water compartments.

- Plastic Construction
- 20Ltr Capacity
- Ideal for Kentucky & Socket Mops
- Side Press Wrings Out Excess Water

Illustrative picture:



Item #5: Bucket, plastic, large

The plastic flexi tub bucket must have a 40 ltr capacity, high density, strong handles, reinforced edges to avoid splitting durability. Flexible plastic handle

Illustrative picture:



Item #6: Disinfectant cleaner

A highly effective, biodegradable disinfectant which kills germs. Concentrated formula must be used neat or diluted to 1:100. Capacity: 5ltr

Item #7: Grab adhesive

Must give excellent adhesion and bonding strength to most solid building materials. Bonds plasterboard, skirting boards, electrical conduit, stone, ferrous and non-ferrous metals.

- For Interior & Exterior Use
- Excellent Bonding Strength Even When Vertical
- Not Water-Resistant

Item #8: Industrial Electric Fan Heater

The industrial fan heater is ideal for industrial applications including workshops, factories, and garages, must have high and low heat settings with adjustable thermostatic control and thermal cut-out overheat protection. Insulated handles must allow for safe handling whilst the heater is still warm.

- Features fan only plus high and low heat settings with adjustable thermostatic control
- Thermal cut-out overheat protection
- Strong steel construction with stand for increased stability
- Supply: 230V 13A
- Max. Output: 3kW
- Dimensions (LxWxH): 302 x 334 x 390mm
- Weight: 5.6kg

Illustrative picture:



Item #9: Mop

350mm pure cotton yarn mop heads. Compatible with aluminium handles.

- Hand Wash
- Cotton
- Highly Absorbent Thick Cotton Strands
- Will Reach into Awkward Corners & Between Grout
- Pack of 5

Illustrative picture:



Item #10: Nails, 75mm, round, masonry

Corrosion-resistant. Bright Zinc-Plated Carbon Steel, 0.5kg pack

Item #11: Pressure washer

A 3-in-1 Multi-Jet lance and a trigger gun with an intelligent LCD display to help change pressure and settings effortlessly for a fast and efficient cleaning on any outdoor surface. Increased cleaning performance with an extra 15bar power with the boost mode. Must get started quickly with the no-mess Plug 'n' Clean detergent system, just clicking the bottle in. Must easily reach every corner with the 10m high pressure hose. Must be designed to adapt instantly to any cleaning task and come equipped with Smart Control Technology. Must connect to a smartphone via Bluetooth for convenient transfer of recommended pressure level from the app to the pressure washer. The app must provide tips on everything to know to take care of the machine.

- 2.8kW Water-Cooled Motor, 230V, 180BAR
- 550Ltr/hr Max. Flow Rate
- 10m High Pressure Hose
- Rotary Power Control
- Adjustable Spray Nozzle
- Water Inlet Filter

- Wheels & On-Board Storage
- 3 Year Manufacturer's Guarantee (T&Cs Apply)
- Bluetooth Connection
- Boost Mode

Illustrative picture:



Item #12: Reciprocating Saw

Cordless 36V reciprocating saw engineered for extremely heavy-duty demolition and cutting to length with minimal vibration and advanced ergonomics

- Base material: Metal, Wood, Brick, Lightweight concrete
- Stroke length: 32 mm
- Stroke rate: 2800 strokes / minute
- Dimensions: 478 x 102 x 147 mm
- Total weight: 3.3 kg

Illustrative picture:



Item #13: TOUGH METALS RECIPROCATING SAW BLADE for item #48

Ultimate carbide-tipped reciprocating saw blade for cutting stainless steel, cast iron and other tough metals thicker than 7 mm (> 1/4")

- Product class: Ultimate
- Shank: 1/2" universal shank
- Teeth per inch: 8

Item #14: NAIL-EMBEDDED WOOD RECIPROCATING SAW BLADES for item #48

Ultimate carbide-tipped reciprocating saw blade for demolishing wood containing hardened metal

- Product class: Ultimate
- Shank: 1/2" universal shank
- Teeth per inch: 5-7

Item #15: FIRE AND RESCUE RECIPROCATING SAW BLADES for item # 48

Longer-lasting reciprocating saw blades for fast, heavy-duty metal cutting in firefighting and rescue work

- Product class: Premium
- Shank: 1/2" universal shank
- Teeth per inch: 10

Item #16: POLYPROPYLENE ROPE BLUE 6MM X 500M

Rotproof, must be supplied on reel.

- Rot-Resistant
- Safe Working Load 420kg
- Polypropylene Construction

Item #17: Screws, mixed size pack

Top quality, waxed single thread, multipurpose woodscrew. Must feature a lower screw-in torque and faster drive speed. Must be suitable for screwdriver, combi drill and impact drivers.

- Carbon Steel
- Excellent for Softwood & Chipboard
- Single Coarse Thread
- Countersunk Head
- 3.5 x 40 (200), 4 x 30 (200), 4 x 40 (200), 4 x 50 (200), 5 x 50 (200), 5 x 60 (100), 5 x 70 (100), 5 x 80 (100) and 6 x 100mm (100).

CE Standard (Tested to EN...)	EN 14592.
Collated/Uncollated	Uncollated

Construction Material (Screws)	Carbon Steel
Drive Type	PZ
Head Type	Countersunk
Manufacturer Guarantee	1 Year Guarantee
Pack Size	1
Pieces in Pack/Case	1400
Resistant Type	Corrosion-Resistant

Item #18: HEAVY DUTY 14MM STAPLE & BRAD TACKER

Lightweight die-cast aluminium housing with anti-jam mechanism. Must feature a rear-loading, open-view magazine and plastic comfort grip. Must have easy squeeze technology to help reduce actuation force. Must use 6, 8, 10, 12 and 14mm staples and 12 and 15mm brads.

- Fires Brads / Staples
- Open-View Magazine
- Die-Cast Aluminium Construction
- Plastic Comfort Grip
- Satin Finish

Item #19: HEAVY DUTY STAPLES ZINC-PLATED 14 X 10MM 1000 PACK

Heavy duty staples must be presented in a handy plastic storage box and be compatible with all major brand heavy duty staplers and tackers. Staple type T50 / G / 140.

Item #20: Submersible pump, electric, solids handling

A heavy duty submersible pump suitable for draining pits, sumps, ditches, footings etc. Can be used for both clean and dirty water applications including water with particles up to 35mm dia. Must include a fitted float switch for automatic water level control. Stainless steel pump body & motor case.

Pumps Solids Up-to	35 mm
Outlet Diameter	1½ "
Max Head	11 m
Volts	230 V
Max Flow	258 L/min
Float Switch	Yes
Watts	1100 W

Use	Clean/Dirty Water
Other Features	Stainless Steel Body

Illustrative picture:



Item #21: Submersible pump, fire hose attachment

The submersible pump must get into every nook and cranny and even pump waste water away with virtually no residue. Must be developed for use under the most difficult conditions even working well in small, cramped spaces, low-lying cellars, under-passes, parking garages, or tight shafts.

Must be equipped with a reliable electric motor, the NAUTILUS is easy to carry and can be deployed wherever large pumps or portable fire pumps cannot go. It can even be quickly and easily transported and operated by just one person.

- NAUTILUS 4/1 with Storz B coupling
- Coupling key ABC DIN 14882
- Firefighting hose B 20, length: 20 m (65.6')
- Outlet pipe B
- B-elbow 90°
- Hose kink protection
- Rope hose holder
- Working rope with carabiner and linen bag, length:
20 m (65.6')
- PRCD-S safety switch
- Wire protection cage with 2 carry handles, can be used as transport and suction protection basket

(dimensions 615 x 455 x 410 mm (24.2" x 17.9" x 17.7"))

- Specially developed for operation with generators from 3 kVA
- Electric motor with a power consumption of 1.84 kVA
- Lower startup current due to weight-optimized plastic impeller
- Supply voltage of 230 V and
1 phase
- Certified according to DIN 14425

Illustrative picture:



Item #22: Taurpaulin, heavy duty, clear, plastic

HEAVY DUTY POLYTHENE SHEET CLEAR 620GA 4 X 3M

620 gauge, heavy duty, clear polythene sheet. Must be folded for ease of handling and use.

Item #23: Taurpaulin, heavy duty, plastic

TARPAULIN SHEET GREEN / BROWN 5 X 8M

Multi-purpose, must offer long lasting protection on even the most demanding of tasks at home, in the garden, or in the workplace. Must have reinforced eyelets to enable a secure fit and give greater protection against wind and rain. Ideal for covering a roof, as a base for rubble collection, covering building materials or logs, as a boat cover and for protection to loads on trucks or trailers. Reversible.

- Water-Resistant
- Tear-Resistant
- Reinforced Eyelets

Item #24: Vacuum cleaner, wet and dry

Must be supplied with moisture-resistant PES filter for capturing 99% of dust before its airborne. Must work with all types of dust and dirt and liquids. Must have air cooling filtration system to help to prolong machine life by cooling down the motor when working in tough conditions. Must features complete conductive system for protection

against ESD shocks. Tool boxes must be stored safely onboard due to flat vacuum head design. Easy to transport.

Air Flow Capacity	74 Ltr/sec
Cable Length	7.5 m
Dry Capacity without Bag	40 Ltr
Manufacturer Guarantee	2 Year Manufacturer's Guarantee
Overall Drum Capacity	40 Ltr
Plug Included	Includes Plug.
Power Output (Watts/Kw)	1380 W
Power Voltage Supply	240 V
Product Height	655 mm
Product Length	560 mm
Product Type	Professional Wet & Dry Vacuum
Product Width	370 mm
Sound Pressure Level	69 dB
Total Product Weight	14.4 kg
Wet Capacity	40 Ltr

Illustrative picture:



Item #25: Wheelbarrow

Wheelbarrow must be highly manoeuvrable and stable on all surfaces. Galvanised body with double-rolled edges for additional strength. Tubular frame must be fully welded and feature a front-tipping nose for easy and safe unloading. Must be ergonomically designed for safe load distribution. 150kg weight capacity.

- 85Ltr Pre-Galvanised Drawn Steel Pan
- Easy Assembly

Illustrative picture:



Item #26: Heavy duty wipes

Heavy-duty wipes for difficult soils from paint splatters and scuff marks to the removal of excess caulk. Must be able to remove oil or water-based paints, adhesives and other substances including silicone sealants, PU foam, oil, tar, grease and permanent marker, as well as general grime from hands, tools and surfaces. Must have resealable lid to prevent wipes from drying out.

Item # 27a to d: LED Lightstick,

LED lightstick for easy identification in water rescue

- Waterproof Silicon construction
- Blink or static On function - 500 hour max run time (on blink)
- Hook and Loop holster (Fits to loop/fluffy patch)
- LED bulb
- Easy to fit and remove
- Dimensions: 11cm x 2.6cm

27a - LED Lightstick, green

27b - LED Lightstick, orange/yellow

27c - LED Lightstick, red

27d - LED Lightstick, white

Illustrative picture:



Item # 28a, b & c: Rope, 10.5/11mm x 15m, EN1891 Type A,

Beal 10.5mm x Top Gun II Unicore (Dry Cover) Dynamic Rope

The Beal Top Gun II Unicore 10.5mm (Dry Cover) rope is a hard wearing all round dynamic climbing rope suitable for beginners, improvers and heavy rope users. The Unicore

technology eliminates sheath slippage making the rope safer and suitable for some industrial applications.

Rope Type	Dynamic
Diameter (mm)	10.5mm
Dynamic Rope Type	Single
Impact Force kN	7.4kN
Number of UIAA Falls	11
Rope Treatment	Dry Cover
Sheath %	40%
Sheath Slippage %	0%
Dynamic Elongation	37%
Length (m)	50m
Weight per Metre	68g

28a - colour black

28b - colour blue

28c - colour green

Item # 29a & b: Lyon Nylon Sewn Sling

Used throughout the work and rescue sectors, sling to enable anchors to be quickly created around a variety of natural and artificial features. The endless loop construction is manufactured from 25mm wide nylon webbing.

Specifications

- Colour: Black with Yellow stitching
- Conformity: EN566 / EN795 Type B
- Breaking Load: 30kN

29a - Length 100cm

29b - Length 200cm