

Annex 3 – Products technical specifications

Item # 1: Wheeled cages for storage of equipment

4-Sided Mesh Roll Cage with Full height door enables the user to safely stack goods inside without the risk of them falling out and either causing damaged or getting damaged themselves.

Illustrative picture:



Dimensions and Specifications:

- 1690H (height) x 735W (width) x 850D (depth) mm
- Internal height measures: 1690 mm
- Ability to hold a load capacity of 600 kgs
- Material in bring zinc plated finish

Item # 2: Chainsaw

Large and powerful chainsaw with a minimum 41" guide bar length. Fuel efficient, the chainsaw should have a stop switch, which will automatically return to run position after the engine is stopped.

Dimensions and Specifications:

- Power source: Gas
- Powerhead weight: Min. 21.8 lbs
- Guide Bar length: 25 inches
- Oilmatic chain: 3/8" RS3
- Chai Oil Capacity: Min. 23.7 Oz
- Engine Power: 8.6 bhp
- Fuel Capacity: Min. 44 Oz.

Item # 3: Concrete saw

Concrete cutter designed for deep cutting and square corners that cuts up to 15.7" deep into concrete and reinforced concrete (with rebar up to 1/2 inch). The concrete saw must include a low exhaust emission engine, HD2 heavy-duty air filter, advanced water controls, low vibration, and a diamond abrasive chain.

Dimensions and Specifications:

- Power source: Gas
- Powerhead weight: Min. 16.8 lbs
- Guide Bar length: Min. 16 inches
- Diamon Abrasive Chain: 3/8" 36 GBM
- Engine Power: 5.8 bhp
- Fuel Capacity: Min. 26.4 oz.
- Displacement: 76.5 cc

Item # 4: Compact Hydrualic lifting cylinder LLCS 50/60 or equivalent

Compact hydraulic lifting cylinder to raise heavy loads. Featuring a pumping up function with a piston to increase the pressure of the hydraulic fluid and use to lower by releasing a spring return. 50 Tons capacity with a minimum 100 mm stroke

Must come with hand jack and hose for compact hydraulic lifting cylinder

Item # 5: Large Jackhammer

Large jackhammer with long work time (at least 4 hours).

Dimensions and Specifications:

Impact energy: 72.8 J
Blows per minute: 870 bpm
Drive shank: 1 1/4" Hex
Net weight: 31.3 kg
Input Wattage 110v: 1,700 w
Input Wattage 240v: 2,000 w

Sound and Vibration:

Noise sound pressure: 96 dB(A)

Noise sound power: 107 dB(A)

Noise K factor: 3 dB(A)

Vibration: Chiselling: 6.5 m/sec²

Vibration K factor: 1.5 m/sec²

Item # 6: Cut Off saw

Cut off saw to be used in cutting metal, concrete and asphalt in commercial applications. Able to cut up to 150 mm deep. With low weight and anti-vibration system.

Specifications:

- Displacement: 98.5 cm
- Power output kW/bhp: 5.0/6.8
- Power output kW: 5
- Weight: 13 kg
- Cut-off wheel: 400 mm
- Max. Cutting depth: 150 mm
- Tank volume: 1,200 ml

Item # 7: Operated Nail gun

Finishing nailer powered by Lithium-Ion battery capable to deliver 800 shots. Magazine with the capacity to carry 110 nails. Nailer to be used in construction site installations applying skirtings, architraves and doorways, and electrical fixtures and plumbing connections,

Featured with a LED job light and belt clip ensuring operator comfort and convenience, together with low vibration and sound level.

Specifications:

- Fastener length: 25-64 mm
- Magazine Capacity: 110 pcs
- Overall length: 296 mm
- Pin Gauge: 16Ga
- Skin Weight: 3.2 kgs
- Voltage: 18V
- Weight: 3.8 kg

Item # 8: 18V Lithium-Ion Cordless Multi-Surface Scanner

Cordless multi-surface scanner capable to locate objects in multiple type of base materials and capable to detect a variety of embedded objects such as metal, wood, plastic, and shielded electrical wire up to 7" deep. Features a LED light.

Item # 9: Ventilation duct carrier

Ventilation duct carrier in Polyethylene.

Specifications:

Diameter: 12"

Length : 25 ft.

Item # 10: Hand cordless chainsaw

Cordless electric cut-off machine for cutting brick, tile and metal. Powered by 36-volt Lithium-Ion battery technology.

Specifications:

- Power Source: Battery
- Weight: 8.6 lbs.
- Maximum cutting depth: 2.75 inches
- Maximum Wheel size: 9 inches
- Arbor size: 0.875 inches

Item # 11: Flat Pry bars

Flat pry bar made of heavy-duty steel which can provide ample leverage to pry apart pieces of flat building material

Size: 5 feet

Item # 12: Shoring raker system

Paratech Light US&R Rescue Strut System 22-796901M or equivalent

Item # 13: Shoring raker system

Shoring system: Paratech US&R Rescue Strut System 22-796900M or equivalent

Item # 14: Shoring raker system

Shoring raker system, timberless : Paratrech Absolute Raker 22-796984 or equivalent

Item # 15: Shoring raker system

Shoring raker system, timberless : Paratrech Absolute Flying Raker 22-796984F or equivalent

Item # 16: Shoring raker system

Shoring raker system: Longshore adjustable brace B23 22-796348

Item # 17: Shoring raker system

Shoring raker system: Longshore adjustable brace B57 22-796350

Item # 18: Ducting for confined space ventilation fan

Vinyl standard Bi-directional duct with cuffs.

Features:

- Vinyl polyester ventilation air duct hose
- 8-inch diameter with external wear strips
- Internal steel reinforced wire hoop 4-inch pitch
- 6-inch long attachment cuff, 8-3/8 inch diameter, with adjustable belt straps on both hose ends
- Maximum temperature rating 180 degree Fahrenheit

Item # 19: Rotary Demolition Hammer

Rotary demolition hammer with active dynamic vibration absorber.

Featuring: Torque limiter. Constant speed control. Ergonomic soft grip. Variable speed control dial. One touch sliding chuck for easy bit installation and removal. LED service and power warning lights. Dual operation mode: Rotary Hammer and Hammer

Specifications:

- Impact energy 19.1 J
- Max in concrete 52 mm
- Impacts per minute 1100 - 2250 ipm
- Input Wattage 1510 w
- Max core diameter (TCT) 160 mm
- Vibration K factor 1.5 m/sec²
- Net weight 11.9 - 12.0 kg

- No Load Speed 150 - 310 rpm
- Vibration: Chiselling 8.0 m/sec²
- Vibration: Hammer Drilling 9.0 m/sec²
- Optimum Drilling Range 25 - 45 mm

Item # 20: Double Level Sliding Compound Mitre Saw

Double Slide Compound Mitre Saw with motor head slides on fixed pipes. Featuring: Front knob for easy bevel adjustment. Holder to support wide workpiece. One-touch sliding lock. Large turn base. Can be connected to dust extractor.

Specifications:

- Blade Diameter 305 mm
- Max mitre range 60 - 60 °
- Max mitre cut at 90° 92 x 382 mm
- Bore Diameter 30 mm
- Max bevel range 48 - 48 °
- Noise sound pressure 91 dB(A)
- Noise sound power 100 dB(A)
- Noise K factor 3 dB(A)
- Input Wattage 110v 1,450 w
- Input Wattage 240v 1,800 w
- No Load Speed 3200 rpm
- Vibration K factor 1.5 m/sec² Vibration 2.5 m/sec²
- Net weight 29.3 kg

Item # 21: Storage boxes, flip top for consumables, pack of 4

Dimensions & Specifications:

- Ext.Top Dim:- 600 x 400 x 365 mm
- Int. Base Dim:- 508 x 346 x 365 mm
- Load:- 165 kg on base tray
- Capacity:- 65 litres
- Weight:- 3.5 kg
- Material:- Polypropylene
- Colour:- Blue

Item # 22: Confined Space Axial Fan

- UL compliant explosion-proof fan designed for use in confined spaces like underground vaults, tanks, open pits, warehouses and basements
- Continuous operation with 115 V, 3.6 A motor with 1/3 HP power output
- Features moulded polyethylene duct inlet and outlet ports capable of accepting 8 / 10 inch hoses
- Can be used as negative or positive ventilation blower with a maximum flow rate of 1390 cfm

Illustrative picture:



Item # 23: Demolition Hammer

Demolition hammer featuring an anti-vibration technology with long size carbon brush and one-touch sliding chuck for easy bit installation and removal. Item should include bull point, bit grease and side handle.

Specifications:

- Continuous rating Inp 1,510W
- Impacts per mn. (ipm) 950–1,900
- Dimensions : 576 x 149 x 265mm
- Net weight: 10.8kg (23.6lbs)
- Power supply cord: 5.0m (16.4ft)

Item # 24: Core drill

Versatile diamond drilling tool for handheld or rig-based coring up to 160 mm (6-1/4"). Able to operate on hand-held or rig-mounted drilling system options.

Specifications:

- Diameter range: 8 - 162 mm
- Base material : Concrete & Masonry
- Number of gears: 3
- No load RPM: gear 1: 840 rpm; gear 2: 1640 rpm; gear 3: 3070 rpm
- Weight according 8.2 kg
- Weight of complete system: 22kg
- Dimensions (LxWxH) 516 x 129 x 159 mm

Item # 25: Cordless circular saw

Circular saw with brushless motor and electric brake. Powered by Lithium batteries. The saw should come with large tool bag.

Specifications:

- Body only machine Voltage: 40V
- Blade Diameter: 185 mm
- Bore: 30 mm
- Noise sound pressure: 92 dB(A)
- Noise sound power: 103 dB(A)
- Noise K factor: 3 dB(A)
- No Load Speed: 6,400 rpm
- Vibration K factor: 1.5 m/sec
- Vibration: Cutting Wood 2.5 m/sec
- Net Weight: 5.6 kg

Item # 26: Twin 18V Brushless Reciprocating Saw

Circular saw with brushless motor and Twin 18V Brushless Reciprocating Saw Powered by two 18V Li-ion batteries in series

Specifications:

- Strokes per Minute (Hi / Lo) 0- 3,000 / 0- 2,300 spm
- Battery Type Lithium-ion
- Body machine ✓
- Voltage 36 (18x2) v
- Capacity in Wood 255 mm
- Capacity in Mild Steel Pipe 130 mm
- Stroke Length 32 mm
- Noise sound pressure 85 dB(A)
- Noise sound power 96 dB(A)
- Noise K factor 3 dB(A)
- Vibration K factor 1.5 m/sec

- Vibration: Cutting Wood 15.5 m/sec
- Vibration: Cutting Chipboard 16.5 m/sec²
- Net weight 4.0 - 4.7 kg

Item # 27: Cordless brushless reciprocating saw

Cordless brushless reciprocating saw with electric brake and electronic 2-speed selection. Variable speed control by trigger. Features a LED job light

Specifications:

- Strokes per Minute (Hi / Lo) 0- 3,000 / 0- 2,300 spm
- Battery Type Lithium-ion
- Voltage 40 v
- Battery Quantity (2.5Ah) 2
- Capacity in Wood 255 mm
- Capacity in Mild Steel Pipe 130 mm
- Stroke Length 32 mm
- Noise sound pressure 85 dB(A)
- Noise sound power 96 dB(A)
- Noise K factor 3 dB(A)
- Vibration K factor 2.0m/sec
- Vibration: Cutting Wood 19.5 m/sec
- Vibration: Cutting Chipboard 18.0 m/sec
- Net weight 4.2 – 4.5 kg

Item # 28: Lever Hoist 3,000 kgs WLL

Lever hoist designed for lifting, pulling, securing and tensioning loads. With desynchronized brake system to guarantee safe use and corrosion resistant load chain. WLL of 3,000 Kgs.

Item # 29: Laser rangefinder

Laser range finder with large range and integrated viewfinder for visibility of laser point up to 250 meters. Featuring options to accurately calculate lengths, volumes, and surfaces. Scope of 250 m and Length of 120 mm.

Item # 30: Timber, sawn

Type: C16
Treated Timber sawn.
Material: Whitewood
Width: 100 mm
Thickness: 100 mmm
Length: 4.8 m
Finish: Raw Sawn

Item # 31: Rotating Lifting Point

Dismountable D-Ring, hexagon-headed screw. 360 degrees rotation. 5000kg WLL

Item # 32: Claw Hammer

Claw hammer to be used in carpentry for driving nails into or pulling them from wood With high-strength fiberglass handle core and non-slip rubber grip. Forged and polished steel head.

Item # 33: Cordless drill hammer

Cordless Brushless Hammer Drill for heavy-duty applications. Compact size with 178 mm long. Electronically controlled motor of 125 N.m of max torque. 2speed transmission 21 clutch settings and drill mode for added fastening control. 3-stage LED gauge to indicate battery charge level. Electric brake for maximum productivity

Specifications:

- Capacity
 - Siding Board: 170 mm (6-11/16")
 - Wood (Auger-Bit): 50 mm (2")
 - Wood (Hole Saw): 152 mm (6")
- Max Fastening Torque
 - Hard / Soft: 130 / 65 N·m (1,150 / 580 in.lbs.)
 - Hard / Soft: 130 / 65 N·m
- Max Lock Torque 125 N·m (1,100 in.lbs.)
- Max Output 680 W
- No Load Speed (RPM)
 - High: 0 – 2,100
 - Low: 0 – 550

- Net weight 2.3 – 2.6 kg (5.1 – 5.7 lbs.)

Item # 34: Timber, sawn

Treated Timber sawn.
Material: Whitewood
Width: 150 mm
Thickness: 50 mm
Length: 4.8 m
Finish: Raw Sawn

Item # 35: Timber, plywood

Structural-grade plywood with a range of uses throughout the building industry.
Width: 1200 mm
Height: 19 mm
Length: 2400 mm

Item # 36: Timber, sawn

Treated Timber sawn.
Material: Whitewood
Width: 100 mm
Thickness: 50 mm
Length: 4.8 m
Finish: Raw Sawn

Item # 37: Anchor Fixing, framing, 210mm, box 50

High-performance plastic anchor for frames (carbon steel, hex head)
Base materials: Concrete (aerated), Concrete (uncracked), Masonry (hollow), Masonry (solid)
Head configuration: Hex head
Material, corrosion: Carbon steel, zinc-plated, Plastic
Size: 210 mm
Box of 50 each

Item # 38: Wire rope winch, 3000kg WLL

Rope hoist with 3,000kg capacity for lifting and puling machines. Comes with 20 meters of wire rope and safety eye hook

Item # 39: Circular Saw

Circular saw equipped with riving knife, electric brake, chip/sawdust ejection port in a durable aluminum base.

Specifications:

- Depth of Cut @ 90° 85 mm
- Blade Diameter 235 mm
- Depth of Cut @ 45° 64 mm
- Bore Diameter 30 mm
- Noise sound pressure 95 dB(A)
- Noise sound power 106 dB(A)
- Noise K factor 3 dB(A)
- Input Wattage 1550 w
- No Load Speed 4500 rpm
- Vibration K factor 1.5 m/sec²
- Vibration: Cutting Chipboard 3 m/sec²
- Net weight 7.2 kg

Item # 40: Heavy-duty Mitre Saw Stand

Heavy-Duty mitre saw stand that can fold away flat for easy storage. With a trolley function which allows easy transportation

Specifications:

- Dimensions (L x W x H): 406 x 1118 x 229 mm
- Weight: 26.3 Kg

Item # 41: Sling, lifting, round

Heavy-duty round sling.
Pack of 5 each
Size: 3 meters.
Capacity 5,000 kg. WLL

Item # 42: Laser Distance Measure

Laser distance measure with range 0.05m to 80m. With multiple measurement functions. Dust and water resistance.

Specifications

- Laser Type Laser class 2: 635 nm
- Measuring range 0.05 – 80m
- Typical Measuring Toleran ±2.0mm/ 10 m

- Max measuring tolerance ± 3.0 mm / 10 m
- Diameter of Laser Point 6 mm / 10 m
- Dimensions (L x W x H) 117 x 53 x 25 mm (4.5" x 2.14" x 1")
- Net Weight 0.14 kg (0.31 lbs.)

Item # 43: Rope Grab

Openable cam-loaded rope clamp for use in haul systems as a tractor or progress capture device. Material: aluminum, stainless steel, nylon

Weight: 260 g

Item # 44: Rope Lifting

Rigging Rope

Specifications:

- 12 mm x 30 m
- Standard: Machinery Directive 2006/42/EC
- Core: polyester
- Cover: polyester

Item # 45: Reciprocating saw blades

Reciprocating saw blades for metal cuttings, medium, 150 mm

Item # 46: Reciprocating saw blades

Reciprocating saw blades for wood cuttings, fast cut, 150 mm

Item # 47: Laser level

Laser running on 12V max battery able to select horizontal/vertical cross lines required for all levelling, aligning and plumbing applications. The line laser has a visibility range of up to 25 metres.

Features:

- LED light blinks if out-of-level
- Pendulum lock
- Pulse power for the receiver
- DC Jack – allows compatibility with LXT batteries if used with a USB adaptor
- 2 Brightness modes (High and Eco)

- Voltage: 12 v
- Laser Colour: Red
- Beam direction/fan angle: Vertical $> 160^\circ$, Horizontal $> 180^\circ$ Range: 25m
- Range with receiver: 80 m
- Self Levelling Accuracy: ± 0.3 mm/m = ± 3.0 mm @ 10m
- Horizontal/Vertical line accuracy: ± 0.3 mm/m
- Operating Temperature Range: -10 - 50 °C
- Storage Temperature Range: -25 - 70 °C
- Net weight: 0.67 - 0.84 kg
- Battery Type: Lithium-ion

Item # 48: Tool Belt

Professional tool belt made with heavyweight poly fabric. Pouches and suspenders can be removed or adjusted for customized tool organization.

Barrel-bottom, reinforced pouches allow extra carrying capacity.

Featuring one steel hammer holder and an additional loop for hammers or other long-handled tools, cats-paw sleeves and a tape measure clip. Infinity belt can be adjusted up to a 52" waist using thick steel grommets.

Item # 49: Anchor Fixing, framing, 110mm, box 100

High-performance plastic anchor for frames (carbon steel, hex head)

Base materials: Concrete (aerated), Concrete (uncracked), Masonry (hollow), Masonry (solid)

Head configuration: Hex head

Material, corrosion: Carbon steel, zinc-plated, Plastic

Size: 110 mm

Box of 100 each

Item # 50: Storage boxes for consumables, flip top 600x400x310mm, pack of 4

Dimensions & Specifications:

- Ext. Top Dim: - 600 x 400 x 310 mm

- Int. Base Dim:- 508 x 346 x 35 mm
- Load:- 165 kg on base tray
- Capacity:- 65 litres
- Weight:- 3.5 kg
- Material:- Polypropylene
- Colour:- Blue

Item # 51: Sling, lifting, round

Heavy-duty round sling.

Pack of 5 each

Size: 2 meters.

Capacity 5,000 kg. WLL

Item # 52: Lyon Nylon Sewn Sling

Used throughout the work and rescue sectors, sling to enable anchors to be quickly created around a variety of natural and artificial features. The endless loop construction is manufactured from 25mm wide nylon webbing.

Item # 53: Adhesive for Tell Tale Crack Monitor

A basic Tell-Tale crack monitoring gauge that monitors horizontal and vertical movement across a crack on a flat surface to an accuracy of +/- 1.0mm and by interpolation to +/- 0.5mm.

Item # 54: Breaker bit, flat blade

Flat blade breaker (20 x 250 mm) bit for use in concrete.

Illustrative picture:



Item # 55: Breaker bit,moil point

Breaker bit,moil points designed for concrete breakers and demolition tools

Item # 56: Scaffold poles

Heavy duty 16ft galvanised steel scaffolding tube, 48.3mm outside diameter with 4mm wall thickness.

Specifications:

- Length 16ft (487cm)
- Outside Diameter 48.3mm
- Wall Thickness 4 mm
- Galvanised Coating 60 micron

Item # 57: Anchor Fixing, drop in for eyebolt, 340kg WLL

High-performance carbon steel tool-set drop-in anchor with metric thread

Thread diameter – 12mm

WLL vertical lifting 340kg

WLL lifting at 45°: 240kg

Coefficient of utilization: 5:1

Item # 58: Gas horn

Free of hydrofluorocarbon gases. To be used for providing temporary cover for alarm installations and construction site applications.

Specifications:

- 112dB Output
- Approx. Range 1500m
- Environmentally Friendly Gas
- Single Non-Flammable Gas Propellant

Item # 59: Rope, Lifting

Rigging Rope

Specifications:

- 12 mm x 15 m
- Standard: Machinery Directive 2006/42/EC
- Core: polyester
- Cover: polyester

Item # 60: Socket set, metric

To handle the toughest industrial applications, provide the best grip on fasteners, and have a superior finish. 27-Piece Premium 6-Point Socket Set, 3/8" Square Drive with

24 Sockets

2 Drive Tools

1 Extension

Standard Sockets: 6 mm, 7 mm, 8 mm, 9 mm, 10 mm, 11 mm, 12 mm, 13 mm, 14 mm, 15 mm, 16 mm, 17 mm, 18 mm, 19 mm

Deep Sockets: 10 mm, 11 mm, 12 mm, 13 mm, 14 mm, 15 mm, 16 mm, 17 mm, 18 mm, 19 mm

7 5/8" Long Ratchet Wrench

8 9/16" Long Flex-Head Wrench Handle

And 6" Long Extension

Item # 61: Anchor fixing, rod, 225mm, box 100

Wedge anchor for cracked concrete and seismic (carbon steel). Material, corrosion:

Carbon steel, zinc-plated

Head configuration: Externally threaded

Drilling Method (AS): Hammer Drilling, Hollow Drill Bit Drilling, Diamond Drilling

Item # 62: Detector hidden wiring and fittings

With automatic calibration to avoid errors. Locate metal and live wire in various wall types as well as wooden substructures in drywall.

Item # 63: Barrier Tape

Red and White Barrier Tapes for notifying of restricted access to hazardous areas or to manage access to work sites.

Specifications:

- 100 meters long
- Made from non-adhesive durable polyethylene

Item # 64: Anchor Fixing, blow out pump

Blow out pump for fast and efficient blowing out of dust and debris from drilled holes to enable proper fixing of anchor and rebar

Item # 65: Sling, lifting, round

Heavy-duty round sling.

Pack of 5 each

Size: 1 meter.

Capacity 5,000 kg. WLL

Item # 66: Fuel cans, unleaded, 20ltrs

20L Scepter Fuel Cans – Olive Drab with Red Strap designed to safely and securely transport auxiliary fuel. Made from rugged HDPE, the fuel can is virtually indestructible.

Item # 67: Hand saw

Durable tooth design and universal hand saw with double bevel-ground, hard-point teeth for cross and rip cutting.

Size: 500 mm

Item # 68: Mole grips set

High grade heat-treated steel alloy construction. Classic trigger release designed to provide maximum locking force. Hardened teeth designed to grip from any angle.

Heat-Treated Carbon Steel Jaws

Steel Metal Handle

Sizes: Small, Medium, and Large

Item # 69: Ratchet straps with hook

Wide Length Ratchet Strap.

Claw Hook Ends.

3 Metres Length

35mm wide ratchet strap

Blue low elongation polyester webbing

Lashing capacity 1000 daN (Kg) when new

Minimum breaking force 2000 daN (Kg) when new.

Claw hooks. Overall length 3 metres, fixed length 0.3 metres

Item # 70: Anchor Fixing, drop in, setting tool

Drop-in anchor setting tool

Illustrative picture:



Item # 71: Tell-Tale crack monitor

With precision silk screened grid.
Both positive & negative graduations marked.
Fine red crosshair allowing accurate estimation to 0.25mm.

Item # 72: Spirit level, 600mm

Constructed from extruded aluminium with ribbed sides. 1 vertical, 1 horizontal and 1 45 degrees vials. Milled top and bottom faces.

Item # 73: Tape measure, metric and imperial (5 meters)

Tape measure with metric and imperial scales. Impact-resistant case, class 2, true-zero 3-rivet hook, spring-return mechanism and bi-material design for comfort and grip.

Item # 74: Nails, 75mm, round wire, flat head

Galvanized, round wire and flat head nails - 75mm

Item # 75: Nails, 90mm, round wire, flat head

Galvanized, round wire and flat head nails - 90mm

Item # 76: Reciprocating saw blades

Reciprocating saw blades for metal cuttings, coarse, 150 mm

Item # 77: Pick Axe

5 LBs Pick Axe and 36" long. High density fibreglass handle, horizontal and vertical chisels and blades for chopping, cutting and grubbing-out ground. Roll-Forged Steel Head. Fibreglass Handle

Item # 78: Nails for nail gun, 90mm

Item # 79: Nails for nail gun, 75mm

Item # 80: Drill bit, timber, set of various sizes, auger bit

Ideal for large diameter drilling in wood.

Specifications:

- 10mm Hex Shank
- Carbon Steel
- Spiral Point

Item # 81: Drill bit, masonry, 20mm

Masonry drill bit 20 x 460 mm
Hardened steel alloy shank with ground tungsten carbide cross tip for clean and accurate holes in brick, concrete, mortar, and stone. Universal compatibility, must fit in most tools

Item # 82: Wrecking bar, gooseneck, medium

Steel gooseneck wrecking bar, medium size

Item # 83: Ratchet strap

Ratchet strap with Delta Rings; 10 m capacity; 5,000 kg.

Item # 84: Hack saw, large

12-Inch-High Tension Hacksaw featuring a rugged design for heavy-duty use and a quick-release, blade changing mechanism in the handle maintains the tension setting, and an easy to access tension guide is on the handle lever.

Item #85: Sledge Hammer

2lb Forged Steel Solid Brass Sledgehammer
Non Sparking Fiberglass Soft Handle

Item #86: Spade

Stainless steel border spade head for general digging. Head measures 23cm long x 14cm wide. Overall height 100cm.

Item #87: Hacksaw

Large wood/metal/plastic hacksaw. 12' (300 mm)

Item #88: Bow shackle, screwpin

Screw pin bow shackles used for lifting applications providing connection to chain.
Size and specifications: 19MM 4.7T Capacity

Item #89: Nail puller (remover), medium

For use to enable quick and easy nail extraction from timber.

Item #90: Saw discs, for timber, 165mm, 24 teeth

Top-performance circular saw blade for wood framing with carbide teeth to cut faster, last longer and maximize your productivity on cordless saws.

Number of teeth: 24

Diameter: 165mm

Item #91: Chisel, hand set

Set of 7 bevel edged chisels, including sizes: 1/8", 1/4", 3/8", 1/2", 3/4" 1", 1 1/2". Set should come with canvas tool roll.

Item #92: Drill bit, masonry, 15mm

Hardened steel alloy shank with ground tungsten carbide cross tip for clean and accurate holes in brick, concrete, mortar and stone. Universal compatibility, must fit most tools.

Item #93: Allen key set, assorted

10 Pieces hand tool Kit Allen wrench. Assorted Key Ring Set

Item #94: Screwdriver set, assorted

Screwdriver Set, Assorted, 12-Piece

Item #95: Gas canister for gas horn

Replacement gas canister for Emergency Gas Horn that complies with the new EU regulations.

Specifications

- Capacity: 200ml
- Pressurised Container

- Non Flammable Gas Charge

Item #96: Drill bit, masonry, 14mm

Hardened steel alloy shank with ground tungsten carbide cross tip for clean and accurate holes in brick, concrete, mortar and stone. Universal compatibility, must fit most tools.

Item #97: Toolbox

Toolbox, Steel, Red, 14 Inch Height

Item #98: Hack saw blade, Junior

20 Pack of 6inch Junior Hacksaw Blades 24 TPI Replacement Saw Blades Saws Tool

Item #99: Lump hammer

Cross Pein Hammer 4 Lb Super Grip

Item #100a-e: Lightsticks

6 inches chemical light sticks with 8 & 12 hours of 360 degrees illumination per stick.
Nontoxic, nonflammable and waterproof.

- Lightsticks, 12hr, green
- Lightsticks, 12hr, red
- Lightsticks, 12hr, yellow
- Lightsticks, 8hr, blue
- Lightsticks, 8hr, white

Item #101: Cutting disc, for metal

Extreme Metal Cutting Disc 115 x 1.3 x 22.23mm

Item #102: Cutting disc, for timber, 184mm, 40 teeth

Ultimate circular saw blade for fine finish in wood, offering more run time for cordless saws

Number of teeth: 40

Diameter: 184mm

Item #103: Hack saw blade, standard, pack of 20

Maintenance Engineered Hacksaw Blade 12" 14-18TPI

Type: Maintenance Engineered

Length: 12 "

Teeth per Inch: 14-18

Material Thickness: 1/4" and Thicker

Application: Aluminum, Babbitt, Brass, Bronze, Non-Ferrous Metals, Cast Iron, Lead, Plastic, Hard Rubber, High-Speed Steel, Tool Steel, Threaded Rod

Item #104: Set square, carpenters, 230mm

Carpenters Square 230mm Hardwood stocks and blued steel blades.

Item #105: Adjustable Pin Spanner Wrench Set

6-Piece Adjustable Pin Spanner Wrench Set

Item #106: Duct tape, silver

Duck Tape, 1-Pack 1.88 Inch x 60 Yard Silver

Item #107: Hack saw, Junior

Heavy Duty Junior Hacksaw, 6 inches, Red

Item #108: Pliers set, assorted

Plier Set: 5 Pliers, Std Cushion Grip, Manual
Illustrative picture:



Item #109: Funnel, for fuel

Large Plastic Automotive Funnel, Long Flexible Spout Extension, Removable Mesh Screen Filter

Item #110: Lubricating oil, 600ml

DW40 Aerosol lubricant 600ml.

Item #111: Water pump pliers

Water pump pliers 10" (254mm)

Item #112: Angle grinder discs, for metal (for Hilti AG150-A36)

Ultimate thin-kerf stainless steel cutting disc for stainless steel and other metals

Product class: Ultimate

Base material: Steel, Stainless steel

Tool type: Angle grinder

Item #113: "Search scanner LEADER SCAN Life Search Equipment (USAR)"

LEADER SCAN Life Search Equipment (USAR)

The Life Search Equipment for use in USAR operations capable of detecting any type of movements during rescue activities. Designed to detect and locate live victims trapped, buried or entombed, following disasters, and able to locate victims by detecting movements at a distance of 30m.

Illustrative picture:



Item #114: Tape Measuring

Compact fibreglass tape of 30 meters with a high impact ABS closed case to withstand severe working conditions. Corrosion-resistant, UV protected and is non-conductive. Washable PVC coating for added durability. 2mm graduations.

Specifications:

ABS Plastic Case

PVC-Coated Fibreglass Blade

Metric & Imperial Scales
 Class 3
 0m Standout Reach
 UV-Resistant
 Barbed Folding Hook

Item #115: Head torch

Compact and powerful headlamp. White or red lighting to preserve night vision and stealth. 350 lumens. The head torch should come with three standard batteries and should also be compatible with a rechargeable battery. Single button for quick and easy selection of brightness or light color. Detachable and washable headband

Specifications:

Brightness: 350 lumens (ANSI/PLATO FL 1)
 Weight: 85 g
 Beam pattern: Mixed
 Energy: Three AAA/LR03 batteries (included) or rechargeable battery
 Watertightness: IPX4 (weather-resistant)

Item #116: Leatherman multi tool EOD Edition

EOD Leatherman Tools Multi-Tools with 15 tools including: Needlenose Pliers, Premium Replaceable Fuse-wire Cutters, Military Performance Spec Cap Crimper, Electrical Crimper, 420HC Combo Knife, Saw, Replaceable Cutting Hook, Hammer, Bolt Override Tool, Replaceable C4 Punch, Replaceable Bronze Carbon Scraper, #8-32 Cleaning Rod/Brush Adapters, Carabiner/Bottle Opener, Large Bit Driver, and Stranded-wire Cutters

Item #117: Groundwork Tools

High quality and robust hand tools for: latrine, pit, trench digging, ground preparation for foundations and road repairs.

Quantity	Unit	Description
----------	------	-------------

10	Each	Shovel, round mouth blade, with handle
10	Each	Spade, square blade, with handle
10	Each	Pickaxe head, chisel and point
10	Each	Pickaxe handle, hardwood
1	Roll(s)	Site marking tape, red/white, 500m
6	Each	Bucket, 16 litre, galvanised steel
6	Each	Rake, 12-tooth head, blade width 280mm, with wooden handles and screws for fixing
5	Each	Miners' bar, chisel and point, 3cm dia. x 1.5m
5	Each	Bolster, length 225mm, blade width 75mm
5	Each	Lump hammer, 4lb
1	Each	Measuring tape, length 30m, width 13mm
2	Roll(s)	Rope, 8mm, polypropylene, length 30m

Illustrative picture:



Item #118: Saw discs, for timber, 184mm, 24 teeth

Standard circular saw blade for fast cutting in construction wood and timber
 Number of teeth: 24
 Diameter: 184,15mm

Item #119: Hand jack and hose for compact hydraulic lifting cylinder

Compatible for items #4 & #120

Item # 120: Compact Hydraulic lifting cylinder LSC 50/60 or equivalent

Compact hydraulic lifting cylinder to raise heavy loads. Featuring a pumping up function with a piston to increase the pressure of the hydraulic fluid and use to lower by releasing a spring return. 496 KN Tons capacity with a minimum 600 mm stroke

Must come with hand jack and hose for compact hydraulic lifting cylinder